

# Technical Information CG-90 Surface Saver Deicer

## **DESCRIPTION:**

CG-90<sup>o</sup> Surface Saver<sup>o</sup> Deicer is an enhanced highway deicing salt product containing a corrosion inhibitor. It is a highly effective performer that creates superior protection against corrosion of exposed metal surfaces, reduced scaling of concrete surfaces, and provides excellent deicing capabilities. Using this product may reduce highway and bridge maintenance costs.

#### **COMPLIANCE:**

CG-90° Surface Saver° Deicer is not approved for human or animal consumption. It is intended for use only as a chemical deicer on roadways and thoroughfares. This product complies fully with ASTM Specification D 632-99 Type 1, Grade 1.

## **ADDITIVES:**

CG-90° Surface Saver Deicer contains a patented corrosion inhibitor and Magnesium Chloride which enhances deicing capability.

#### APPLICATION:

CG-90° Surface Saver° Deicer should be applied at the same rate as regular highway deicing salt.

# HANDLING AND STORAGE:

CG-90° Surface Saver° Deicer requires no additional handling, equipment or labor over and above that used for regular highway deicing salt. To improve caking resistance and reduce run-off, it is recommended that the product be stored in a covered storage shed or tarped. Normal precautionary measures for the safe handling of deicers should be observed.

## PACKAGING:

CG-90° Surface Saver<sup>©</sup> Deicer is available in bulk and one-ton bags.

## **CARGILL SALT**

P.O. Box 5621 Minneapolis, MN 55440 METHODS OF ANALYSIS:

Methods of analysis are taken from the ASTM designations D 632-99, E 534-98 and G 31-72, from SHRP H205 and from Cargill.

#### **CHEMICAL ANALYSIS:**

Component	Units	Typical	Specification
Sodium Chloride	%	77.1	75.0 min.
Magnesium Chloride <sup>1</sup>	%	21.9	-
Corrosion Inhibitors	%	1.0	1.1 max.

#### SIEVE ANALYSIS:

U.S.S. Mesh	Opening Inches	Opening Microns	Typical	Specification
1/2″	0.500	12700	100	100 min.
3/8"	0.375	9525	97	-
4	0.187	4760	55	-
8	0.0937	2380	38	-
30	0.0232	590	8	15 max.

Note: Sieve analysis is reported as percent passing.

## PRODUCT BENEFITS:

Average % protection against salt induced corrosion
Lowest effective deicing temperature
Deicing rate (as compared to sodium chloride)
Reduces surface scaling of concrete

90%
14.9°F (-9.5°C)
1.5X

PRODUCING LOCATIONS: VARIOUS LOCATIONS ACROSS THE U.S.

No. 7703 Revised May 2000

NOTICE: All of the above statements, recommendations, suggestions and data are based on out laboratory results, and we believe same to be reliable. Nevertheless, with the exception of data showing an express guaranty (such as in the case of products specifically designed for use as nutrient supplements), all such statements, recommendations, suggestions and data hereinabove presented are made without guaranty, warranty or